



	Monster	Monster+
ENGINE		
TYPE	Testatretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled	Testatretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled
DISPLACEMENT	937 cc (57 cu in)	937 cc (57 cu in)
BORE X STROKE	94 mm x 67.5 mm	94 mm x 67.5 mm
COMPRESSION RATIO	13.3:1	13.3:1
POWER	111 hp (82 kW) @ 9,250 rpm	111 hp (82 kW) @ 9,250 rpm
TORQUE	9.5 kgm (93 Nm, 69 lb ft) @ 6,500 rpm	9.5 kgm (93 Nm, 69 lb ft) @ 6,500 rpm
FUEL INJECTION	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system
EXHAUST	Pre-muffler and twin muffler, catalytic converter and 2 lambda probes	Pre-muffler and twin muffler, catalytic converter and 2 lambda probes
TRANSMISSION		
GEARBOX	6 speed	6 speed
PRIMARY DRIVE	Straight cut gears, ratio 1.85:1	Straight cut gears, ratio 1.85:1
RATIO	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24
FINAL DRIVE	Chain, front sprocket z15, rear sprocket z43	Chain, front sprocket z15, rear sprocket z43
CLUTCH	Slipper and self-servo multiplate wet clutch with hydraulic control	Slipper and self-servo multiplate wet clutch with hydraulic control
CHASSIS		
FRAME	Aluminum alloy Front Frame	Aluminum alloy Front Frame
FRONT SUSPENSION	Ø 43 mm usd fork	Ø 43 mm usd fork
FRONT WHEEL	Light alloy cast, 3.5" x 17"	Light alloy cast, 3.5" x 17"
FRONT TYRE	Pirelli Diablo Rosso III 120/70 ZR17	Pirelli Diablo Rosso III 120/70 ZR17
REAR SUSPENSION	Progressive linkage, preload adjustable monoshock, aluminium double-sided swingarm	Progressive linkage, preload adjustable monoshock, aluminium double-sided swingarm
REAR WHEEL	Light alloy cast, 5.5" x 17"	Light alloy cast, 5.5" x 17"
REAR TYRE	Pirelli Diablo Rosso III 180/55 ZR17	Pirelli Diablo Rosso III 180/55 ZR17
WHEEL TRAVEL (FRONT/REAR)	130 mm / 140 mm (5.1 in / 5.5 in)	130 mm / 140 mm (5.1 in / 5.5 in)
FRONT BRAKE	2 x Ø 320 mm semi-floating discs, radially mounted Brembo M4.32 monobloc 4-piston callipers, radial master cylinder, Cornering ABS	2 x Ø 320 mm semi-floating discs, radially mounted Brembo M4.32 monobloc 4-piston callipers, radial master cylinder, Cornering ABS
REAR BRAKE	Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS	Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS
INSTRUMENTATION	4.3" TFT colour display	4.3" TFT colour display
DIMENSIONS AND WEIGHTS		
DRY WEIGHT	166 kg (366 lb)	166 kg (366 lb)
KERB WEIGHT*	188 kg (414 lb)	188 kg (414 lb)
SEAT HEIGHT	820 mm (32.3 in)	820 mm (32.3 in)
	800 mm (31.5 in) (accessory low seat)	800 mm (31.5 in) (accessory low seat)
	775 mm (30.5 in) (accessory low seat + low suspension kit)	775 mm (30.5 in) (accessory low seat + low suspension kit)
WHEELBASE	1,474 mm (58.0 in)	1,474 mm (58.0 in)
RAKE	24°	24°
TRAIL	93 mm (3.7 in)	93 mm (3.7 in)
FUEL TANK CAPACITY	14 l (3.7 US gal)	14 l (3.7 US gal)
NUMBER OF SEATS	2	2
EQUIPMENT		
SAFETY EQUIPMENT	Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light	Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light
STANDARD EQUIPMENT	Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators, USB power socket	Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators, USB power socket, Flyscreen, Passenger seat cover
READY FOR	Ducati Multimedia System, Heated grips	Ducati Multimedia System, Heated grips
WARRANTY AND MAINTENANCE		
WARRANTY	24 months, unlimited mileage	24 months, unlimited mileage
MAINTENANCE SERVICE INTERVALS	15,000 km (9,000 miles) / 12 months	15,000 km (9,000 miles) / 12 months
DESMOSERVICE	30,000 km (18,000 miles)	30,000 km (18,000 miles)
EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies)		
STANDARD	Euro 5	Euro 5
CO2 EMISSIONS	n/a	n/a
CONSUMPTION	n/a	n/a

*Kerb weights indicate total bike weight with all operating consumable liquids and a fuel tank filled to 90% of capacity (as per EU Regulation 44/2014

** Not available in Canada, China, Japan